

Optional Accessories

IR Unit



WA-IR25 / WA-IR35 / WA-IR60

	WA-IR25	WA-IR35	WA-IR60
Type	Day & Night IR Illuminator		
Number Of Infrared LED	50ea Infrared LEDs	70ea Infrared LEDs	140ea Infrared LEDs
Wave Length	850 nm		
Angle Of Infrared LED	20 - 45 Combinations		
Illuminate Distance	Outdoor 25 M Max.	Outdoor 35 M Max.	Outdoor 60 M Max.
Power Supply	DC 12V / 600 mA	DC 12V / 850 mA	DC 12V / 1700 mA
Operation Temperature	-10 to 45 degree °C.		
Weight	Approx 0.5Kg	Approx 0.7Kg	Approx 1.08Kg

Bracket



WA-VCT31A

Type	Camera Bracket
Max. Load	5 Kg
Material/Color	Aluminum
Dimension	130 mm (H)
SWIVEL ANGLE	360°
TILT ANGLE	90°

Dome Housing



WA-CDH60N

Type	CCTV Half Dome Housing 5-inch / 6-inch.
Material/Color	PMMA / Light brown
Slant	60° - 90° angle
Transmission Ratio	96%
Aberrance	≤ 0.16

Housing



WA-MT68B

Type	Camera Bracket
Max. Load	5 Kg
Material/Color	Aluminum
Dimension	130 mm (H)
SWIVEL ANGLE	360°
TILT ANGLE	90°
IP (Ingress Protection)	IP68

Housing



WA-TS81
WA-TS81B/24V
WA-TS81BIR/24V

	WA-TS81B/24V	WA-TS81BIR/24V
Type	Outdoor Back Open Camera Housing with Blower	Outdoor Back Open Camera Housing with Blower and IR
Material/Color	Aluminum / Beige	
Appearance Size	142(W)X115(H)X370(L)mm	
Suitable Camera Size	100(W)X80(H)X300(L)mm	
Number Of Infrared LED	-	22 ea Infrared LEDs
Illuminate Distance	-	10 - 15 M
Control Temperature	Blower "ON" : 35 degree °C / "OFF" : 25 degree °C	
Input Voltage	24VAC	

Lens



WV-LZA63/3H



WV-LZA61/2S

3x Variable, F0.95 (wide), F1.7 (Tele)	2x Variable, F1.4 (wide), F1.8 (Tele)
2.8 - 8 mm, CS-Mount.	3.8 - 8 mm, CS-Mount.
37 x 34 x 46 mm	60.5 x 53 x 45.3 mm

Lens



WA-VF358CE



WA-VF2812CE



WA-VF550CE



WA-VM2812CE

	WA-VF358CE	WA-VF2812CE	WA-VF550CE	WA-VM2812CE
Type	Full Metal 1/3" Vari-Focal			
Focal Length	3.5 - 8 mm (2.2x)	2.8 - 12 mm (4.2x)	5 - 50 mm (10X)	Full Metal 1/3" Vari-Focal Mega Pixel 2.8 - 12 mm (4.2x)
Relative Aperture	F1.4	F1.2	F1.4	F1.4
Iris system	Automatic focus (DC)			
Angular Field of View	95° - 44° 35'	109° - 35° 30'	62° 24' - 6° 50'	92° - 27° 12'
Mount Type	CS-Mount			
Back focal length	12.526 mm			
Minimum Object Distance	0.3m			