



Smart look Day/Night Fixed Dome Camera with advanced features

Key Features

- High resolution: 600 TV lines
- High sensitivity with Day/Night (electrical) function: 0.08 lx (Color), 0.07 lx (B/W) at F1.4
- ABS (Adaptive Black Stretch) enhances visibility of dark area without degrading image quality in bright area.
- Adjustment features including ATW (Auto Tracing White Balance)
- 3-dimensional color conversion function for natural color reproduction even in lower color temperature situation
- Adaptive Digital Noise Reduction: Integration of 2D-DNR and 3D-DNR ensures noise reduction in various conditions.
- Internal synchronization
- Wide coverage : Horizontal:77 °, Vertical: 57 °
- Lens Distortion Compensation
- 2-way hinge (horizontal and vertical) for easy installation
- Smart look fits for various applications such as shopping mall, hotels and hospitals.


Standard Accessories

- | |
|--------------------------------------|
| • Operating Instructions 1 pc. |
|--------------------------------------|


Specifications

TV System	PAL		
Camera	Image Sensor	1/3 type interline transfer CCD	
	Effective Pixels	976 (H) x 582 (V)	
	Scanning Mode	2:1 interlace	
	Scanning Area	4.8 (H) x 3.6 (V) mm	
	Scanning Frequency	Horizontal: 15.625 kHz Vertical: 50.00 Hz	
	Horizontal Resolution	600 TV lines	
	Minimum Illumination	Color : 0.08 lx(color mode) at F.1.4 B/W : 0.07 lx (Black-and-white mode) at F.1.4	
	Signal-to-Noise Ratio	52 dB (AGC: OFF)	
	White Balance	ATW (2,700 ~ 6,000 K)	
	Light Control	ELC (Auto IRIS)	
	AGC	ON	
	Day & Night (Electrical)	Auto	
	Digital Noise Reduction	ON	
Synchronization	Internal (INT)		
Lens	Focal Length	3.6 mm	
	Angular Field of View	H: 77°, V: 57°	
	Maximum Aperture Ratio	1:1.8	
	Focusing Range	0.4m ~ ∞	
	Video Output	1.0 V [p-p] PAL composite video signal 75 Ω	
General	Safety / EMC Standard	CE(EN55013 , EN55020)	
	Power Source and Power Consumption	12 V DC ,120mA	
	Ambient Operating Temperature	-10 °C ~ +50 °C (14 °F ~ 122 °F)	
	Ambient Operating Humidity	90 % or less (without condensation)	
	Dimensions	ø108 x 88 mm (H)	
	Mass (approx.)	200g	
	Finish	ABS resin / Sail White	

Part Names and Functions



Appearance



Important

– Safety Precaution: carefully read the operating instructions and installation manual before using this product.

DISTRIBUTED BY:

- All TV pictures are simulated.
- Weights and dimensions are approximate.
- Specifications are subject to change without notice.
- These products may be subject to export control regulations.

Panasonic[®]

<http://panasonic.net/security/>

Printed in Japan (2A-098A)